


KLLVB

Valbocht voor KLL



Te bevestigen met:



Zelfborgende moer en bout
VM

Radius: 300 mm

Stand. Uitv.

Sendzimir

Mat. Opt.

Hot-Dip

Mat. Opt. PE

Poedercoating

HD	Artikel	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
HD	KLLVB60.150	60	146			1,528	1		STK
HD	KLLVB60.200	60	196			1,629	1		STK
HD	KLLVB60.300	60	296			1,830	1		STK
HD	KLLVB60.400	60	396			2,032	1		STK
HD	KLLVB60.450	60	443			2,133	1		STK
HD	KLLVB60.500	60	496			2,234	1		STK
HD	KLLVB60.600	60	596			2,435	1		STK
HD	KLLVB85.150	85	145			1,922	1		STK
HD	KLLVB85.200	85	196			2,083	1		STK
HD	KLLVB85.300	85	296			2,284	1		STK
HD	KLLVB85.400	85	396			2,486	1		STK
HD	KLLVB85.450	85	445			2,587	1		STK
HD	KLLVB85.500	85	496			2,688	1		STK
HD	KLLVB85.600	85	596			2,889	1		STK
HD	KLLVB110.150	110	145			2,934	1		STK
HD	KLLVB110.200	110	196			2,755	1		STK
HD	KLLVB110.300	110	296			2,956	1		STK
HD	KLLVB110.400	110	396			3,158	1		STK
HD	KLLVB110.450	110	445			3,259	1		STK
HD	KLLVB110.500	110	496			3,360	1		STK
HD	KLLVB110.600	110	596			3,561	1		STK

Minimum aantal bouten en moeren VM6.10: 8 stuks.