


KLLB

Horizontale bocht voor KLL



Te bevestigen met:



Zelfborgende moer en bout
VM

Radius: 300 mm

Stand. Uitv.

Sendzimir

Mat. Opt.

Hot-Dip

Mat. Opt. PE

Poedercoating

HD	Artikel	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
HD	KLLB60.150	60	141			1,659	1		STK
HD	KLLB60.200	60	191			1,898	1		STK
HD	KLLB60.300	60	291			2,375	1		STK
HD	KLLB60.400	60	391			2,852	1		STK
HD	KLLB60.450	60	443			3,091	1		STK
HD	KLLB60.500	60	491			3,329	1		STK
HD	KLLB60.600	60	591			3,806	1		STK
HD	KLLB85.150	85	145			2,053	1		STK
HD	KLLB85.200	85	195			2,378	1		STK
HD	KLLB85.300	85	295			2,897	1		STK
HD	KLLB85.400	85	395			3,415	1		STK
HD	KLLB85.450	85	445			3,675	1		STK
HD	KLLB85.500	85	495			3,934	1		STK
HD	KLLB85.600	85	595			4,453	1		STK
HD	KLLB110.150	110	145			3,065	1		STK
HD	KLLB110.200	110	195			2,826	1		STK
HD	KLLB110.300	110	295			3,384	1		STK
HD	KLLB110.400	110	395			3,940	1		STK
HD	KLLB110.450	110	445			4,219	1		STK
HD	KLLB110.500	110	495			4,498	1		STK
HD	KLLB110.600	110	595			5,055	1		STK

Minimum aantal bouten en moeren VM6.10: 8 stuks.